

## **Intermediate Bulk Containers**

All reconditioned Intermediate Bulk Containers marked UN31HA1, of capacity 275 - 330 gallons US, and supplied with plastics caps must be closed for shipment using the closures and gaskets supplied by the manufacturer and according to the following instructions:

- 1. Place cap (6" or 9"), with rubber gasket installed, on opening of IBC bottle.
- 2. Turn the cap clockwise to engage the threads.
- 3. Depending upon the manufacturer, as identified on the bottle, tighten caps to:
  - a. Encore- 50 ft-lbs
  - b. Greif- 45 ft-lbs
  - c. Mauser- 70 ft-lbs
  - d. Schutz- 75 ft-lbs
- 4. If present, 2" plugs (with gasket) should be tightened to 20 ft-lbs.
- 5. If present, <sup>3</sup>/<sub>4</sub>" plugs (with gasket) should be tightened to 9 ft-lbs.

## **Plastic Open Head Drums**

All open head plastic drums marked UN1H2, of capacity 20 - 59 gallons US, and supplied with plastic lids and locking rings must be closed for shipment using the closures and gaskets supplied and according to the following instructions:

- 1. Place drum lid on top opening and ensure that drum chime is under gasket area.
- 2. Place locking ring over cover and secure lid.
- 3. If present, 2" plugs (either self sealing or with gasket) should be hand tightened plus an additional quarter turn.
- 4. If present,  $\frac{3}{4}$ " plugs (either self sealing or with gasket) should be hand tightened plus an additional quarter turn.

## **Plastic Tight Head Drums**

All tight head plastic drums marked UN1H1, of capacity 20 - 59 gallons US, and supplied with plugs and gaskets must be closed for shipment using the closures and gaskets supplied and according to the following instructions:

1. Install 2" Buttress and/or 2" NPT plugs (with gasket) in the corresponding drum opening and tighten to 25 ft-lbs.

Effective Date: 05/06/2019 Approved By: C. Key